



CENTRAL CONTROL UNIT (CCU)

The CCU is to be installed inside the Traffic Cabinet and is powered by the AC supply mains (115 VAC). The CCU is the power supply and signaling interface between the existing Intersection Traffic Control Unit and the Push Button Stations which are located in the field. One CCU can control up to 12 Push Button Stations. The CCU controls up to four Pedestrian phases, receiving its timing from the Walk and Don't Walk signals. Additional advanced configurations can be obtained by utilizing its general purpose Inputs and Outputs. All Inputs and Outputs have full optical isolation and include Transient Voltage Protection.

Ped Walk / Don't Walk Inputs:

Optically Isolated 80–150 Volts AC/DC 5mA Maximum

General Purpose Outputs & Ped Outputs:

Optically Isolated 36 Volts AC/DC Peak

.3A Solid State Fused Contact Closure

Fault Output:

Normally Open and Closed Relay Contacts 125 Volts AC/DC 1A Maximum

A, B, C, D PBS Power Outputs:

Nominal 22 Volts DC, Short Circuit Protected – Auto Recovering

General Purpose Inputs:

10 – 36 Volts AC/DC Peak 10mA Maximum, Optically Isolated

Environmental:

Operating and Storage –30°F (–34°C) to 165°F (74°C) 0–100% Humidity Non-Condensing

Interface cable included but not shown

INFORMATION ON THIS DOCUMENT IS PROPRIETARY TO POLARA AND SHALL NOT BE USED, COPIED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT WRITTEN CONSENT OF POLARA.

Revised – 08/21/08														
										4115 W. ARTESIA AVE. FULLERTON, CA. 92833				
										TOLERANCES: .XXX ±.005 .XX ±.02 (EXCEPT AS NOTED)				SCALE 1:1
		DRAWN BY BB		CKR.		ENG. MGR.		MFG. MGR.		SHEET 1 OF 1				
		DATE 03-14-03		DSN. ENG.		Q.A. APP.		FINAL APP.		USE 2W NAV				
TITLE										DWG. NO.				
2 WIRE NAVIGATOR										CCU				
CENTRAL CONTROL UNIT														
REV.	DATE	LTR	E.C.O. NO.	BY	CKR	ENG	DSN	MFG	QA	FNL				